


报价单

Quotation

Citybus -NJL6128EV-High-floor





NJL6128EV 高地板系列 NJL6126EV High-floor Series						
外形尺寸 (mm) Dimensions (mm)	11990×2550×3300	制动距离(m) (V=30Km/h 满载) Braking distance (m) (V=30Km/h full load)	≤10			
车厢内高(mm) Internal height (mm)	≥2100	最大爬坡度(%) Maximum gradability (%)	≥20			
轴距 (mm) Wheelbase (mm)	6050	最小转弯直径(m) Minimum turning diameter (m)	≤24			
前悬/后悬(mm) Front overhang/rear overhang (mm)	2680/3260	整备质量(Kg) Curb mass(Kg)	11700-13650(具体以公告 为准) 11700-13650 (subject to announcement)			
前轮距/后轮距(mm) Front wheel track/rear wheel track (mm)	2050.2097,2119/1840, 1860,1882	最大总质量(Kg) G.V.W.(Kg)	18000			
最小离地间隙(mm) Minimum ground clearance (mm)	116	额定乘员(人) Rated passenger capacity (persons)	95/10-49(具体以公告为 准) 95/10-47 (subject to announcement)			
接近角/离去角(°) Approach angle / departure angle (°)	8	标配座位数(个) Standard number of seats (pcs)	44+2+1 Can be customized according to customers			
系统	项目	标配供应商	备注			
系统 System	坝目 Project	你能供应商 Suppliers	角注 Remars			
电池 battary	CATL 422.9KWH	•	行驶里程 350kM Drive range 350KM			

3Ky Wett					
		CATL 326.7KWH	0		行驶里程 250kM Drive range 250KM
		skysouth 423.936KWH			行驶里程 350kM Drive range 350KM
		skysouth 326.861KWH	0		行驶里程 250kM Drive range 250KM
	整车控制器 VCU	南京金龙整车控制器 Nanjing Jinlong vehicle control unit	•		
	集成控制器 Integrated Control Unit	五合一系统 Five-in-One System	•		
新能源 New Energy	电机类型(额定功率) Motor type (rated power)	永磁同步电机 Permanent magnet synchronous motor	•	朗高 3500 LEGO 3500	
	电机冷却系统 Motor cooling system	自清洁 ATS 电子冷却系统 Self-cleaning ATS electronic cooling system	•		铝制水箱 Aluminum water tank
		水泵 Water pump	•		
	打气泵 Air compressor	电动打气泵总成 Electric air compressor assembly	•		
		无油活塞电动打气泵 Oil-free piston electric air compressor	0		
	转向泵 Steering pump	永磁同步双源电动转向泵 Permanent magnet synchronous dual source electric steering pump	•		
	前桥 Front Axle	前桥 7.5T	•	汉德 HD	
		Front Axle 7.5T	0	东风、方盛 DF, Fangsheng	
	后桥 Rear Axle	后桥 13T	•	汉德 HD	
		Rear Axle 13T	0	东风、方盛 DF, Fangsheng	
底盘 Chassis	免维护轮端 Maintenance-free	后桥免维护 Maintenance-free rear axle	•		后桥脂润滑、3 年质保 Rear axle grease Iubrication, 3-year warranty
	wheel end	前桥免维护 Maintenance-free front axle	0		
	主减状态 Main minus status	新能源专用主减 New energy dedicated main reducer	•		
	转向 Steering	国产液压助力转向 Domestic hydraulic power steering	•		
	悬架结构 Suspension Structure	6 气囊空气悬架 6 Air bellow air suspension	•		
	悬架控制系统 Suspension Control	机械高度阀控制系统 Mechanical Height Valve Control System	•		
	System	ECAS 系统 ECAS system	0		

前盘后鼓双回路气制动系统 Front disc barke and rear drum brake, 行车制动 Driving Brake 前盘后盘双回路气制动系统	
Driving Brake 前盘后盘双回路气制动系统	
Front and rear disc brake, dual circuit air braking system	
压差式自动放水阀 Differential pressure automatic water release valve	
Drain valve 电控放水阀 Electronically controlled water release valve	
钢制储气筒	
Air Storage Cylinder 铝合金储气筒 Aluminum alloy air reservoir 机械手刹	
驻车制动 Mechanical handbrake 电子手刹 ○	
Electronic handbrake 辅助制动 能量回收制动 Auxiliary Brake Energy recovery brake	
#	
Brake Valves Brake body valves 克诺尔、WABCO Knorr, Wabco 科密	
ABS ABS ABS WABCO WABCO	
铝合金轮辋 轮辋 Aluminum alloy rim ●	
Rims (8.25×22.5)普通轮辋 (8.25×22.5) Regular rim 上海双钱	
Doublecoin 普利司通、韩 泰、佳通、米其 林、固特异、朝 阳、万力 Bridgestone, Hankook, Giti, Michelin, Goodyear, Arisun, Wanli	
胎压监测 Tire pressure monitoring	
整车润滑系统 Complete vehicle lubrication system 集中润滑 Centralized lubrication ●	
车身 车身结构 Body — 承载式车身 Monocoque body ●	
Bodywork Structure 铝合金车身 Aluminum alloy body	

	踏步 Steps	4 级踏步 4-Step	•	
	乘客门	前中双内摆门(内置摆臂) Front and middle double inward swing doors (built-in swing arm)	•	
	Passenger door	前内摆门、中塞拉门 Front inward swing door, middle sliding door	0	
	前风窗 Front windshield	夹胶全景玻璃 Laminated panoramic glass	•	
	后风窗 Rear windshield	钢化玻璃 Tempered glass	•	
-	侧窗 Side windows	内置式推拉窗 Built-in sliding window	•	
-	司机窗 Driver's window	内置式推拉窗 Built-in sliding window	•	
外饰	外后视镜	手动调节 Manual adjustment	•	
Exterior Decoration	Outside rearview mirror	电动调节 Electric adjustment	0	
	后视镜加热 Heating for rear mirror	电除霜 Electric defrost	0	
	玻璃颜色 Glass color	绿玻 Green glass	•	
	侧舱门 Side hatch	铝舱门 Aluminum hatch	•	
	舱门锁 Hatch lock	三角锁 Triangle lock	•	
	后舱门 Rear hatch	铝合金后舱门 Aluminum alloy rear hatch	•	
	流水槽 Water channel	一体式流水槽 One-piece water channel	•	
	油漆 Paint	素色漆 Plain paint	•	
	冷风管道 Cold air duct	铝合金,无广告灯箱,双列 LED 灯 Aluminum, no AD box, dual LED light	•	
内饰 Interior Trims	安全天窗 Roof escape hatch	2 个带换气扇天窗 2 roof ecape hatch with ventilation fan	•	
	地板	PVC 地板 PVC flooring	•	
	Flooring	竹胶板 Bamboo glue board	0	
	地板革	石英砂阻燃地板革+黄色踏步 Quartz sand flame retardant floor covering + yellow step	•	标配不含"站立禁区"字样 Standard specification does not include the words "standing forbidden area"
	地似早 Floor covering	石英砂阻燃地板革+黄色踏步(带站立禁区) Quartz sand flame retardant floor covering + yellow step (with standing forbidden area)	0	

	乘客座椅	公交座椅		
	Passenger seats	Bus seat		
	司机椅 Driver's seat	气囊减震绒布司机椅 Airbag shock-absorbing velvet driver's seat	•	头枕分离 Head restraint separation
		气囊减震绒布司机椅 Airbag shock-absorbing velvet driver's seat	0	高靠背 High backrest
	司机包围 Separating facility for driver's compartment	铝合金 Aluminum alloy	•	
		灰色钢管喷塑 Gray steel pipe spraying	•	无滚花 Without knurling
	扶手 Handrails	儿童标高线 Child elevation line	•	下单时提供客户需求尺寸 Provide the size required by the client when placing order
		不锈钢扶手 Stainless steel handrail	0	
		铝合金扶手 Aluminum alloy handrail	0	
	下客门铃 Get-off request bell	2 个 2 pcs	•	
	内后视镜 Interior rear view mirror	大方镜 Large square mirror	•	
	吊环 Ring	20 个三角吊环 20 triangular rings	•	
	司机遮阳帘	司机前撑杆式遮阳帘 Driver's front strut type sun visor	•	
	Driver's sun visor	司机侧导轨卷帘式遮阳帘 Driver's side rolling shutter type sun visor	•	
		冲孔铝塑板 Perforated aluminum composite panel	•	
	内顶板 Interior roof panel	PVC 板 PVC panel	0	
		铝合金悬浮内顶 Aluminum alloy suspended inner top PVC 板	0	
	侧围板 Side panels	PVC panel 铝塑板	•	
	窗帘	Aluminum composite panel 侧窗帘	0	
	Curtains CAN 总线	网图巾 Side curtains 整车 CAN 总线	0	
电器 Electrical equipment	CAN BUS	一般 CAN BUS for entire bus 普通配电盒	•	
	低压配电系统 Low voltage distribution system	General distribution box 全铝防火智能低压配电系统	•	
		All-aluminum fireproof intelligent low- voltage power distribution system	0	

	雨刮器	双摆雨刮器	•		
	Wiper	Double swing wiper			
	蓄电池 Low voltage batteries	24V 2×100Ah	•		
	电子钟	带温度计)		
	Electronic Clock	With thermometer	0		
		手动			
	电脑报站器	Manual	•		
	Computerized bus	GPS 自动			
	stop annunciator		0		
		GPS automatic			
	管理系统	新能源智能管理系统	_		
	Management System	New Energy Intelligent Management	•		
		System			
	倒车蜂鸣器	标配 -	•		
	Reverse buzzer	Standard			
		新国标记录仪	•		
	行驶记录仪	New national standard recorder			
	Driving recorder	前路况+脚踏板+司机面部			
	2111119 10001401	Front road conditions + foot pedals +	•		
		driver's face			
		司机、前乘客门+整车			
		Driver, front passenger door + whole	•		
		bus			
	监控系统	中乘客门+倒车+独立显示			
	Monitoring System	Center passenger door + reverse +	•		
		independent display			
		远程监控终端	0		
		Remote Monitoring Terminal			
		坡道辅助(HAS)Hill assist system			
		(HAS)			
		AutoHold	•		
		倒车雷达	0		
		Reversing radar		O	
	N 4 / N = 1 + 1 1 = 1 + 1 + 1 + 1 + 1 + 1 + 1 +	360 环视系统	_		
	安全辅助装置 Safety	360 Around View System	0		
	assistance devices	安全驾驶辅助系统			
		Safety Driving Assistance Systems	0		
		电子后视镜			
		电力冲线器 Electronic Rearview Mirror	0		
		客流量统计系统			
		台加里切り 示切 Passenger flow statistics system	0		
		快换充电插座			
	(大狭た电描注 Quick change charging socket	•		
	便捷使用装置 Easy-to-use devices				
	Lasy-to-use devices	一键启动	0		
		One-touch start			
	路牌	LED 前、后路牌(16 点阵, 8 字节)			
		LED front and rear signs (16 dot matrix,	•		
		8 bytes) LED 侧路牌(16 点阵,8 字节)			
	Line and destination	LED 侧路牌(16 点阵, 8 子卫) LED side sign (16 dot matrix, 8 bytes)	0		
	signs	车内滚动屏(16 点阵, 8 字节)			
		丰内成幼卉(10 总阵,8 子口) Internal scrolling screen (16 dot matrix,	0		
		8 bytes)			
		O Dytes)			

3Ky Wett					1
	空调 Air Conditioning	冷暖空调(3.2 万大卡)+热管理 Heating and cooling air conditioning (32,000 calories) + thermal management	0		
		单冷空调+热管理 Single cooling air conditioner + thermal management	•	ketai	
	司机风扇 Driver's Fan	A 柱 A pillar	•		选装电子后视镜时取消 Canceled when selecting electronic rearview mirrors.
	除霜器	高压电除霜器 High voltage electric defroster	•		IP67
	Defroster	水暖除霜 Water heating defrost	0		使用独立水暖时采用水暖 除霜
	暖风 Warm wind	独立水暖 Independent plumbing	0		Use water heating defrost when using independent plumbing.
	扬声器 Speakers	椭圆形 Oval shape	•		
	视听系统 Audio-visual system	MP3	0		预留喇叭 Reserved speaker
	USB	司机 USB Driver USB	•		
	随车工具 Tools supplied with bus	开沃汽车专用随车工具 Special tools supplied with Skywell bus	•		
	垃圾桶 Trash cans	不锈钢垃圾桶 Stainless steel trash can	0		
	杂物箱 Sundries box	不锈钢杂物箱 Stainless steel grocery bin	0		
	清洁设施 Cleaning facilities	吹灰装置 Ash blowing device	•		
		普通投币机 Regular coin machine	•		
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	投币机 Coin machine	带电子锁投币机 Coin machine with electronic lock	0		
设施设备 Facilities and Equipment		带假币识别投币机 Coin machine with counterfeit currency identification	0		
	IC 卡机 IC card machine	智能 IC 卡机 Intelligent IC card machine	0		
	安全锤 Safety Hammer	防盗报警安全锤 7 只(带钢丝绳)+司机 侧防盗报警安全锤 1 只 (不带钢丝绳) 绳) Anti-theft alarm safety hammer 7 pcs (with wirerope) + Driver's side anti-theft alarm safety hammer 1 pcs (without wirerope)	•		
	消防装置	2 个 4Kg 干粉灭火器 2 x 4Kg dry powder fire extinguishers	•		
	Fire fighting devices	电池舱自动灭火装置 Automatic fire extinguishing device for battery compartment	•		

		高压舱自动灭火装置 Automatic fire extinguishing device for high-voltage compartment	•			
		电池箱内灭火装置 Fire extinguishing device inside battery box	0			
	轮椅辅助装置 Wheelchair assistance devices	残疾人电动升降装置 Disabled electric lifting device	•			
		客舱喷淋系统 Passenger compartment sprinkler system	0			
	车内安全装置 Safety devices inside bus	易燃易挥发物检测 Flammable and volatile material detection	0			
		车载测温仪 On-board thermometer	0			
	ē示标配,"〇"表示选配 Jeans standard, "〇" mear	ns optional				
报价(此价格不含认证费用)			(CATL 422.9KWH		
	his price does not	CIF caldera 美元 元 CIF caldera dollar		CATL 326.7KWH		
include certif	fication fees)			south 423.936KWH south 326.861KWH		
商务条件/Co	ommercial terms	车款 30%预付款, 70%发运前支付; For the products: 30% advance payment, 70% to be paid before the delivery.				
		整车 2 年或 12 万公里,先到为准; 2 years or 120,000km which comes first for Comple vehicle				
质保/Warranty		电池质保 8 年或 50 万公里; 8 years or 500,000km which comes first for battery				
		电机电控质保 5 年 20 万公里; 5 years or 200,000km which comes first for motor and controller				
据价日期 2024 年 7 月 12 日,有效期自报价日期之后 30 天; Quotation date is 12 July. 2024, the validity is 30 days from the date of quotation; 如汇率波动超过 2%,卖方有权相应调整价格; The seller reserves the right to adjust the price if the fluctuation of the exchange rate 2%;				·		
	The specific	「单配置需与卖方确认,卖方保留针对技力 cation should be confirmed with the seller b Reserves the right of final interpretation of	efore	the order to be place		